



K25 - MIX

**HARD CHROME
OVER STAINLESS
STEEL CONSTRUCTION**

DUAL AIR REGULATORS

**25:1 RATIO AIR-
LESS UNIT**



**HIGH DELIVERY
RATE OF .5 GPM AT
60 CYCLES**

**K1 MIX OR K1 3A
MIX GUN WITH
VARIOUS TIP SIZES**

**ADJUSTABLE
SPRAY PRESSURE
UP TO 2850 LBS**

**THE ATOMIZATION AIR IS BLENDED WITH FLUID AT THE TIP'S OUTLET
ALLOWING A VERY STABLE AND EVEN SPRAY PATTERN, UNIFORM FILM
BUILD AND SUPERIOR FINISHES WITH GREATER TRANSFER EFFICIENCY.
COMBINES THE ADVANTAGES OF AIRLESS AND AIR SPRAYING.**

**HIGH SPEED OF APPLICATION AND FLUID DELIVERY WITH A SUPERIOR
FINISH QUALITY**

EXTREMELY EFFICIENT METHOD TO APPLY TOPCOATS

- 142500smc** **K 25 - MIX** **Hard Chrome over stainless steel pneumatic piston pump with dual regulator (pump and gun air adjustment). Anodized pump body. Shut off air valve. Cart Mounted, Stainless steel wet parts and fittings. Fluid suction set for 5 gal. pail. Complete with K1 MIX Gun, tip, and 25' air and fluid hoses.**
- 142501smc** **Same as above-on WALL MOUNTING BRACKET**
- 142501sm** **UNIT ONLY - on WALL MOUNTING BRACKET**
- 142502 smc** **Same as above - K1 3A MIX GUN (reversing tip for ease of tip-clog removal), CART MOUNTED**
- 142503 smc** **Same as above - with K1 3A MIX GUN ON WAL L MOUNTING BRACKET**



K1 3A MIX GUN



K1 MIX GUN

VOLUME PER CYCLE (CC) (OZ) 22 0.78	DELIVERY (I/MIN) (G.P.M.) 3 0.8	MAX. FLUID PRESSURE (BAR) (PSI) 200 2.850	MAX.AIR PRESSURE (BAR) (PSI) 8 115	WORKING PRESSURE (BAR) (PSI) 8 115	AIR CONSUMP- TION (I/MIN) (C.F.M.) 190 6.65	WEIGHT (KG) (LB) 25 55
---	---	--	---	---	---	------------------------------------

A.O.M. - AMERICA

54 S. Commerce Way

Suite 180

Bethlehem, PA 18017

800-533-6254 Fax: 610-954-5532

<http://www.aomspray.com>

Accuspray & AOM Canada Inc.

2612 Ch. Mt-Echo

Knowlton, Quebec J0E 1V0

Tel: 450-242-1004/800-465-2325

Fax: 450-243-5232

Email: accuspray@qc.aibn.com



Distributor: