



NOZZLE CHART

STANDARD FLUID NOZZLES

PRESSURE FEED

MATERIAL	FLUID NOZZLE NO.
ULTRA LIGHT / Reduced flow	(.020" Dia.) 0.5mm
VERY LIGHT / Reduced flow	(.030" Dia.) 0.8mm
LIGHT: less than 15 to 20 seconds in ZAHN 2 Cup, e.g., stains, varnishes, thin lacquers, automotive refinishing materials.	(.040" Dia.) 1.0mm (.046" Dia.) 1.2mm (.051" Dia.) 1.3mm
MEDIUM: 20 to 60 seconds in a ZAHN 2 Cup, e.g., general industrial coatings.	(.055" Dia.) 1.4mm (.059" Dia.) 1.5mm (.063" Dia.) 1.6mm
HEAVY: greater than 60 seconds in a ZAHN 2 Cup.	(.067" Dia.) 1.7mm (.071" Dia.) 1.8mm

SIPHON FEED

LIGHT to MEDIUM materials Auto body spot repairs	(.055" Dia.) 1.4mm
MEDIUM to HEAVY materials Auto body overall finishing	(.067" Dia.) 1.7mm

GRAVITY FEED

LIGHT: 15 to 20 seconds in a ZAHN 2 Cup, e.g., stains, varnishes, thin lacquers, automotive refinishing materials	(.046" Dia.) 1.2mm (.051" Dia.) 1.3mm (.055" Dia.) 1.4mm
MEDIUM: 20 to 60 seconds in a ZAHN 2 Cup, e.g., general industrial coatings.	(.059" Dia.) 1.5mm (.067" Dia.) 1.7mm (.071" Dia.) 1.8mm